

# The KBH HB1350 Hopper Bottom Trailer



## Durable Steel Construction!

- ▶ 12 gauge sheet metal throughout
- ▶ Vertical tubing support columns
- ▶ More structural steel than any other trailer in the industry!
- ▶ Longer lasting return on your investment



**BUILT IN THE KBH**  
**“EXTRA STRENGTH”**  
**TRADITION.**

**(800) 843-5241**  
**www.KBHequipment.com**

*The*  
**KBH**  
CLARKSDALE ★ MS  
*Corporation*

# HB1350 HOPPER BOTTOM TRAILER



- ▶ Outstanding 25" clearance (empty)
- ▶ Smooth operating rack and pinion doors
- ▶ Large 27" X 21" door openings

All new running gear ▶

Heavy-duty leaf spring suspension ▶



## HB1350 SPECIFICATIONS

Length:	40 feet
Width:	96 inches
Height:	73" sides, 12 gauge
Weight:	13,320 lbs. (empty)
Hopper Capacity:	1,350 cubic feet – two compartments
Hopper Clearance:	25" (empty)
Hopper Slopes:	End/floors: 33° Sides: 37°
Hopper Doors:	27" X 21" openings – rack and pinion
Top & Bottom Rail:	4" X 3" X 3/16" tubing
Sidewall Support:	(5x) 4" X 3" X 3/16" tubing
Ladders:	Front and rear
Tarp:	Shur-Lok roll tarp (high UV yellow)
Suspension:	Hutch 9700 48,000 lb.
Axles:	Hendrickson/Dana 22,500 lb. tandem axle
ABS Brakes:	One axle, 2 sensors and modulator valve
Wheels:	8.25" X 24.5"
Tires:	New 11R X 24.5" radial tires
Landing Gear:	Two-speed landing gear with tubing dolly pad
King Pin:	16" from front
Coupler Height:	49"

▶ 2-speed landing gear with 10" X 2" tubing flotation dolly pad

***From the manufacturer  
you've trusted for  
more than 50 years!***

**(800) 843-5241**  
**www.KBHequipment.com**